

MOWO Premium Designer Flooring (Specification Data)

PATCHTONE & GRAINETTE & OAKLACE & INKPLAY COLLECTION

Type of Construction:	Commercial Grade 9" Loose Lay Luxury Vinyl Tile	
Use:	Commercial	
Size:	9" Width X 60" Length (228.6mm X 1524mm)	
Installation Method:	Glue Down	
Certification:	FloorScore Certified by SCS Global Services	
Wear Layer:	20mil (0.5mm)	
Edge Detail:	Beveled Edge	
Emboss:	Natural Wood Texture	
Gauge:	5mm Total Thickness	
Planks/Case:	6	
Coverage/Each Plank:	3.77 Sq. Ft. (0.35 Sq. Meters)	
Coverage/Case:	22.6 Sq. Ft. (2.1 Sq. Meters)	
Coverage/Pallet:	52 Cases/Pallet (1175.2 Sq. Ft. / 109.2 Sq. Meters)	
Warranty:	20-Year Limited Commercial	

STANDARDS - SAFETY & PERFORMANCE

Standard	Standard Feature	Performance
Standard		9 in*60 in*0.5mm
ASTM E648	Critical Radiant Flux	Passes - >0.45 watts/cm², Class 1

ASTM D2047	Coefficient of Friction, Slip Resistance	Meets SCOF for ADA walking surfaces
CDPH/EHLB, Standard Method v1.2	VOCs/TVOCs, Formaldehyde	Refer to Standard

STANDARDS - SOUND

Standard	Description	Requiremen	ts	Results
ASTM E90 & ASTM E413	Airborne Sound Transmission Loss of Building Partitions and Elements (STC / Sound Transmission Class)	6" Concrete Slab + Drop-Ceiling	STC ≥ 50	STC 62 (Surpasses Requirements)
ASTM E492 & ASTM E989	Impact Sound Transmission Through Floor-Ceiling Assemblies (IIC / Impact Insulation Class)	6" Concrete Slab + Drop-Ceiling	IIC ≥ 50	IIC 54 (Surpasses Requirements)

STANDARDS - MANUFACTURING & USAGE

Standard	Feature	Performance	
Stallualu	reature	9 in*60 in*0.5mm	
ASTM F970	Static Load	Passes - 1000 psi	
ASTM F2199	Dimensional Stability	Passes	
ASTM F1914	Residual Indentation	Passes	
ASTM F1514	Resistance to Heat	Passes - less than 8.0 Delta E.	
ASTM F1515	Resistance to Light	Passes - less than 8.0 Delta E.	
ASTM F925	Resistance to Chemicals	Passes - no change	

MOWO Loose Lay Luxury Vinyl Plank Flooring Specification Data

ASTM F410	Wear Layer	Passes
ASTM D4060	Abrasion Resistance	Passes
ASTM D7027	Hoffman Scratch	Passes
EN 16094	Micro-Scratch Resistance (A & B)	Passes

Recommend Installation Options:





